



Atkinson & Kirby

Real Wood Flooring for Professionals

Uniclass L532: P511	EPIC E411: X52/3
CI/SfB (43)	Hi3



Diamond Range
Pre-Finished Hardwood Flooring





ATKINSON & KIRBY LTD HAVE BEEN PRODUCING HARDWOOD FLOORING FOR OVER 100 YEARS, AND OUR REPUTATION PRECEDES US. WE PRIDE OURSELVES ON ONLY MANUFACTURING AND SUPPLYING QUALITY HARDWOOD FLOORING AND ACCESSORIES AND PRESENTING THEM TO OUR CUSTOMERS WITH THE HIGHEST LEVELS OF CUSTOMER SERVICE AND EFFICIENCY. ALL OUR PARTNER MILLS ARE VISITED REGULARLY TO ENSURE THAT THEY MEET OUR STANDARDS AND TO ENSURE THAT PRODUCT QUALITY IS MAINTAINED. THE DIAMOND RANGE DEMONSTRATES THE NATURAL BEAUTY OF A REAL WOOD FLOOR WITH THE CONVENIENCE OF A PRE-FINISHED STRIP, AND ITS LUXURIOUS FINISH SIMPLY EXUDES QUALITY.

Antique Naval Oak

DIAMOND SOLID RANGE

FINISHED WITH SEVEN COATS OF UV CURED SEAL, DURABILITY REALLY IS THE KEY.

WHATEVER THE SURROUNDINGS, BE IT CONTEMPORARY AND MINIMALIST OR COSY AND TRADITIONAL, DIAMOND SOLID HAS SOMETHING TO MEET EVERY SPECIFICATION.



Walnut Natural

DIAMOND MULTI-LAYER RANGE

THE LOOK AND FEEL OF A SOLID FLOOR WITH ALL THE ADVANTAGES OF A MULTI-LAYER.

AVAILABLE IN THREE THICKNESSES 14MM HICKORY, 18MM WHITE OAK AND WALNUT AND 22MM WHITE OAK.

14MM HICKORY IS HAND CARVED FOR AN ANTIQUE, AGED APPEARANCE AND ITS BEAUTIFUL GOLDEN COLOUR MAKES IT TRULY DISTINCTIVE.





DIAMOND MULTI-LAYER RANGE

COMBINING THE BEAUTY OF A SOLID BOARD WITH THE PRACTICALITIES OF AN ENGINEERED, 22/6 IS THE ULTIMATE FLOORING PRODUCT.

WITH A 6MM HARDWOOD WEAR LAYER IT CAN BE SANDED AND SEALED JUST AS MANY TIMES AS YOU WOULD EXPECT TO BE ABLE TO DO WITH A SOLID BOARD.

22/6 IS AVAILABLE UNFINISHED, UV OILED OR BRUSHED AND UV OILED.

22/6 White Oak UV Oiled 189mm

DIAMOND SOLID SPECIFICATIONS

SOLID

7 coats of UV cured seal which contains ceramic particles and gives a high resistance to scratching.

Thickness: 18mm

Length: Random (Average varies according to species)

Face Width: Various (83-150mm depending on Species)

Tongue, grooved and end matched

Micro bevelled edges on all 4 sides.



White Oak Select



Antique Oak



Extra Antique Oak



Antique Naval Oak



Ipe



Walnut Natural

DIAMOND MULTI-LAYER SPECIFICATIONS

14MM HICKORY SPECIFICATION

Thickness: 14mm

Width: 127mm

Length: Random (Average 700mm)


Wear Layer: 3mm

Plywood core.

Tongue, grooved and end matched

Micro bevelled edges

Finish: Hand carved. 7 Coats of UV lacquer.



Antique Hickory

18MM SPECIFICATION

Thickness: 18mm

Width: 127mm

Length: Random (Average varies according to species)

Wear Layer: 4mm

Plywood core.

Tongue, grooved and end matched

Micro bevelled edges

Finish: 7 Coats of UV cured seal.



Walnut Multi-Layer



White Oak Multi-Layer

22/6MM SPECIFICATION

Thickness: 22mm

Width: 189mm or 220mm

Length: 1860mm (189mm) or 1830mm (220mm)

Wear Layer: 6mm

Plywood Core: 220mm wide

Softwood Core: 189mm wide

Tongue, grooved and end matched

Micro bevelled edges

Finish: UV Oiled, Brushed & UV Oiled or Unfinished.



White Oak Multi-Layer

TECHNICAL INFORMATION

GRADE DESCRIPTIONS

Prime / Select

This is the highest grade containing predominantly heartwood but containing some sapwood. And provides a floor with a generally uniform appearance. Allow for small burs and equivalent characters such as tight checks and it will be as the timber produces.

Natural A flooring product that contains the natural character of the timber, will contain variations in colour and varying characteristics. Open characters such as checks and knotholes are admitted but must be sound and readily filled.

MAINTENANCE GUIDANCE

The Diamond Range is suitable for use in Commercial and Domestic situations. As with all Hardwood Floors maintenance is the key to lifelong service and beauty.

Wood will mature with age, some colours will change and get a richer tone by exposure to UV light (sunlight).

By following these simple maintenance guidelines you will maintain the natural beauty of the floor. You should always remember, wood is a natural product; its looks will improve as the floor matures.

By following these simple guidelines your Atkinson & Kirby Hardwood Floor will remain attractive and give many years of use.

ROUTINE MAINTENANCE

Dirt and Grit are the enemies of all Wooden Floors. Make sure that a sturdy doormat is in place both inside and outside all exterior access doorways. Sharp objects can damage your floor. Always protect the floor by using felt pads on furniture legs. Don't forget that pet's claws, stiletto heels and sharp objects can scratch and damage the floor.

VACUUM & DAMP CLEAN

Use a Vacuum cleaner on a daily basis. This will remove Dirt and Grit and prevent it from scratching the floor surface. For more thorough cleaning use a damp mop or cloth with a light spray of Atkinson & Kirby Finitec Cleaner. Remember, you must never use too much water on wooden floors. Standing water should be removed immediately.

STAINS

As with all floor coverings stains should be removed whilst they are still wet. After removal of the stain wipe the floor with a clean damp cloth.

REPAIRS

Small nicks and scratches can be touched up using our colour-matched fillers. For slightly larger areas a small amount of our Touch-Up sealer can be mixed with the filler. In the case of larger areas of damage the floor can be sanded and resealed. Only a suitable expert should carry out this type of work.

RE-SEALING / REJUVENATING

After a period of time you may find that in some areas (entranceways, high traffic areas etc.) the floor starts to look dull. In the first instance use Atkinson & Kirby's Refinisher. For best results this should be used with our Refinisher Applicator.

With correct maintenance your Hardwood Floor will give many years of use, adding a warmth and beauty.

Supplies of Atkinson & Kirby maintenance products are available from your local supplier.

IMPORTANT DO'S AND DONT'S

DO

- Clean the floor regularly.
- Wipe up any spilt liquids immediately (wood will absorb liquids and expand).
- Use protective pads under all furniture legs.
- Use barrier mats at all external doors.
- Protect your floor from grit.
- Keep the ambient temperature to 20°C.
- Use a DAMP mop to clean the floor.

DON'T

- Allow liquid to stand on the floor, this can cause the wood to expand.
- Use abrasive cleaners, these will damage the seal.
- Allow sharp or abrasive objects to come into contact with the floor. Please note that stiletto heels and pet's claws may damage hardwood flooring.

For further information on fitting and maintenance, please contact your hardwood flooring supplier or Atkinson & Kirby direct.

Other ranges also available:

Traditional Range Solid Unfinished Hardwood Flooring

Contract Range Solid and Multi-Layer Pre-Finished Hardwood Flooring

Platinum Range 15mm Pre-Finished Multi-Layer Hardwood Flooring

Platinum Clic 15mm Pre-Finished Glueless Multi-Layer Hardwood Flooring

Platinum Fine Line 15mm Contemporary Pre-Finished Multi-Layer Hardwood Flooring



Discounts for
CFA members.



Atkinson & Kirby

Real Wood Flooring for Professionals

Head Office:

Atkinson & Kirby Ltd., Atkinson Road,
Ormskirk, Lancashire, L39 2AJ

T +44 (0) 1695 573234 **F** +44 (0) 1695 586902

London Office:

Atkinson & Kirby Ltd., Unit 4, Inwood Business Centre,
Whitton Road, Hounslow, Middlesex, TW3 2EB

T +44 (0) 208 577 1100 **F** +44 (0) 208 577 0400

E sales@akirby.co.uk **W** www.akirby.co.uk